

The LCi-RTS100 Is Built To An Uncompromising Set Of Standards—Which Also Got It THX® Ultra2 Certified

For absolutely the best, most consistent home theater performances, the LCi-RTS100 is the new standard for in-home entertainment. **It's The First And Only In-Ceiling Speaker To Be Awarded THX® Ultra2 Certification**, which means you're assured a great surround sound performance and exceptional dynamic range.

- **Integrated Performance Enclosure**—The LCi-RTS100 features an integrated “perfect volume” performance enclosure to ensure superb performance every time.
- **Ideal For Retrofit And New Construction**—The LCi-RTS100 installs easily in new or post construction projects.
- **Stud-Lock Mounting System™** (patent pending-included) is an aluminum frame that locks the speaker in place, taking all the weight and stress off the drywall and transferring those forces to the studs or joists. The system increases bass performance, as well as clarity, and reduces unwanted structure borne vibration.
- **THX® Ultra 2-Certified** means you're assured of great surround sound performance and exceptional dynamic range.
- **Audiophile Grade Drivers And Tweeters**—We've incorporated the same driver technologies found in our highly acclaimed LSi and LCi series of freestanding and built-in speakers.
- **Aerated Polypropylene Dynamic Balance® Cones** (two 5 1/4" drivers) have lower excursion rates and therefore less distortion for better sound. They're stiff yet lightweight for superb midrange clarity, punchy bass and high efficiency.
- **Ring Radiator Tweeter.** The ring radiator design, found in \$35,000 free standing speakers, delivers smooth, extended highs with excellent accuracy and astonishing detail.
- **High-Quality Crossover Networks** assure seamlessness to reproduce always inspiring performances.
- **The LCi-RTS100 Ships With Two Grilles**—One cloth grille for maximum sonic performance, one aluminum mesh for a more traditional appearance. Perforated metal grilles can cause diffraction. Our specially designed 3-piece grille assemblies, using aluminum mesh, provide a 75% open area for superior on-and off-axis response.
- **Room Environment Controls**—Refined wall distance and tweeter control switches ensure the LCi Reference Theater Series always performs at its best regardless of location and surroundings.
- **MSRP: \$1250 each**



Angled baffle geometry ensures directed imaging to the listening area.

Specifications

Recommended Amplification (W/channel)	10-200W
Impedance(Nominal)	4 Ohms
Frequency Response (+/-3dB)	50Hz-27kHz/80Hz-26kHz
Sensitivity (1w/1m)	92 dB
Overall Diameter	14" (35.56cm)
Cutout Diameter	12 1/2" (31.75cm)
Overall Depth	8 3/4" (22.23cm)
Mounting Depth (assumes 1/2" drywall)	8 1/4" (20.9cm)
Speaker Weight	12.50 lbs. (5.67kg) each

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.

